



LED Pop-Up Lights



TRADE SHOWS
EXHIBITIONS
INDUSTRY FAIRS
DISPLAY ADS



Pop-Up Lights

Pop-Up Lights are widely used in exhibition events such as industry fairs, exhibition shows and trade shows.

Pop-Up lights are very simple to install and are usually installed in on Advertisement Displays such as Standees and Roll-up Banners to enhance the effects of the display

The long arms of the pop-up lights provide a very good lighting effect in exhibitions.

SPECIFICATIONS

	Model No. SL-025-08-42L	Model No. SL-025-08-60L
LED Type	SMD 5630	SMD 5630
LED Qty	42	60
Power	24W±10%	30W±10%
Current Range	0.8A	0.8A
Input Voltage	18V/26V	30V/36V
Lumen	1800Lm±10%	2400Lm±10%
Color Temperature	2700~7000K	2700~7000K
Beam Angle	68°	68°
DIM	NO	NO
CRI	≥70	≥70
Power Efficiency	≥80%	≥80%
Color	• Black • Silver	• Black • Silver
Main Material	AL+Iron+ABS	AL+Iron+ABS
Size	L478*W146*H35 mm	L478*W172.5*H35 mm
Connector	DC Plug	DC Plug
Installation	AL Clamp	AL Clamp
Working Temperature	-20°~60°	-20°~60°

Trade Show Display Spot Light

Model No. SL-025-08-42L
Model No. SL-025-08-60L



SAMPLE APPLICATION:



Housing Colors Available:



SPECIFICATIONS

	Model No. SL-2067-NCOB200
LED Type	COB
LED Qty	1
Power	20W±10%
Input Voltage	AC85-265V
Lumen	1800Lm±10%
Color Temperature	4000~5000K
Beam Angle	68°
DIM	NO
CRI	≥80
Power Factor	≥0.9
Color	• Black • Silver
Main Material	AL+Iron+ABS
Size	L478*W146*H47 mm
Connector	3 Pin Plug
Installation	Universal Shoe
Working Temperature	-20°~60°

COB Trade Show Display Spot Light

Model No. SL-2067-NCOB200

Housing Colors Available:



SAMPLE APPLICATION:



Pop-Up Lights

Pop-Up Lights are widely used in exhibition events such as industry fairs, exhibition shows and trade shows.

Pop-Up lights are very simple to install and are usually installed in on Advertisement Displays such as Standees and Roll-up Banners to enhance the effects of the display

The long arms of the pop-up lights provide a very good lighting effect in exhibitions.

SPECIFICATIONS



Model No. SL-1100-03-78L

LED Type	Φ5 LED
LED Qty	78
Power	7W±10%
Current Range	1.5A
Input Voltage	DC12V
Lumen	450Lm±10%
Color Temperature	NW/CW
Beam Angle	68°
DIM	NO
CRI	≥70
Power Efficiency	≥80%
Main Material	AL+Iron+ABS
Size	L453*W266*H35 mm
Connector	DC Plug
Installation	AL Clamp
Working Temperature	-20°~60°

SPECIFICATIONS



Model No. SL-001-78L

LED Type	Φ5 LED
LED Qty	78
Power	7W±10%
Input Voltage	DC12V
Lumen	≥450Lm
Beam Angle	60°
DIM	NO
CRI	≥70
Power Efficiency	≥80%
Main Material	Iron+ABS
Size	L505*W160*H35 mm
Connector	DC Plug
Installation	Iron Clip
Working Temperature	-20°~60°

Pop-Up Lights

Pop-Up Lights are widely used in exhibition events such as industry fairs, exhibition shows and trade shows.

Pop-Up lights are very simple to install and are usually installed in on Advertisement Displays such as Standees and Roll-up Banners to enhance the effects of the display

The long arms of the pop-up lights provide a very good lighting effect in exhibitions.



**Trade Show Display
Spot Light**

Model No. SL-006-78L

Housing Colors Available:



SAMPLE APPLICATIONS:



LED Pop-Up Lights

ENERGY SAVING
ENVIRONMENT FRIENDLY
LONG LIFE SPAN
SMART DESIGN



SPECIFICATIONS

Model No. SL-006-78L

LED Type	Ø5 LED
LED Qty	78
Power	7W±10%
Current Range	1.5 A
Input Voltage	DC12V
Lumen	450Lm±10%
Color Temperature	2700-7000K
Beam Angle	60°
DIM	NO
CRI	≥70
Power Efficiency	≥80%
Main Material	AL+Iron+ABS
Size	L535*W140*H35 mm
Connector	DC Plug
Installation	AL Clamp
Working Temperature	-20°~60°

Roll-Up Lights

Roll up display lights are designed to highlight specific areas of a roll up display. With this, advertisers can make sure that audiences can easily view the entire presentation with the illumination tool.



Roll-Up Light

Model No. SL-1050-5W

Housing Colors Available:



SPECIFICATIONS

	<i>Model No. SL-1050-5W</i>
LED Type	LED GU10
LED Qty	1
Power	5W±10%
Input Voltage	AC850265V
Lumen	280Lm±10%
Color Temperature	2700~7000K
Beam Angle	40°
DIM	NO
CRI	≥70
Power Efficiency	≥80%
Main Material	Q235+Iron
Size	L540*W87*H54 mm
Connector	Direct Input
Installation	AL Clamp
Working Temperature	-20°~60°



Roll-Up Light

Model No. SL-1058L-5W

Housing Colors Available:



SPECIFICATIONS

	<i>Model No. SL-1058L-5W</i>
LED Type	LED MR16
LED Qty	1
Power	5W±10%
Current Range	0.42A
Input Voltage	DC12V
Lumen	280Lm±10%
Color Temperature	2700~7000K
Beam Angle	40°
DIM	NO
CRI	≥70
Power Efficiency	≥80%
Main Material	Zinc Alloy+Iron+AL Clip
Size	L340*W50*H27 mm
Connector	DC Plug
Installation	SL-0515 AL Clamp
Working Temperature	-20°~60°



Accessories for your display

Choose the right clamp for display



Forward Slider



Mounting Plate (Silver)



0509 AL Clamp (Silver)



Reverse Slider



Mounting Plate (Black)



0509 AL Clamp (Black)



0505 AL Clamp



0520 AL Clamp



T Slider

Accessories for your display

Choose the right clamp for display



Universal Shoe + Forward Slider



Universal Shoe + 0520 AL Clamp



Universal Shoe + 0509 AL Clamp



Universal Shoe + 0505 AL Clamp



Other Industry Applications for LED Lighting



OFFICES



RETAIL



EVENTS



**PRIVATE
COLLECTIONS**



HOMES

**A GREENER
CAUSE FOR A
BETTER COST**

KNOW MORE ABOUT US

www.illuminatingasia.com

<https://www.facebook.com/illuminatingasia>

<https://twitter.com/iaspl>

HAVE QUERIES?

Drop us an email at sales@illuminatingasia.com

or

Talk to us at (65) 9336-0324